



your local global brand

Formula GVX 5W-30

Synthetic MID SAPS Motor Oil

Product Description

Gulf Formula GVX 5W-30 is the latest low emission synthetic engine oil exclusively developed to meet the requirements of the entire range of passenger cars of Volkswagen running on Ultra low Sulfur fuel. It has been designed to deliver outstanding performance for extended drain intervals.

Remark: not suitable for R5- en V10 TDI engines and engines where VAG norm VW 506.01 is being advised.

Gulf Formula GVX 5W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Low Ash content reduces particulate build-up in DPFs and helps in extending the regeneration intervals
- Latest mid SAPS additive technology reduces poisoning and degradation of catalyst and prolongs life of after treatment devices
- Outstanding thermo-oxidative stability reduces deposits & sludge build-up and facilitates extended oil life
- Exceptional low temperature fluidity aids cold start and protects against wear at start-up
- Excellent antiwear property protects against engine wear and facilitates extended engine life

Gulf Formula GVX 5W-30 exceeds the following performance criteria

Approved VW 504.00/507.00 MB-Approval 229.51 BMW LL-04
Porsche C30

Exceeds ACEA A3/B4, C3

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m ³	ASTM D4052	843
Kin. Viscosity @40°C	mm ² /s	ASTM D445	69.8
Kin. Viscosity @100°C	mm ² /s	ASTM D445	11.6
Viscosity index		ASTM D2270	169
Viscosity CCS@-30°C, max	cP	ASTM D2983	6600
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-42
Total Base Number	mgKOH/g	ASTM D2896	6.6
Sulphated Ash	%Wt	ASTM D874	0.68

Product Code: 1205	Date Issued: 13-08-2012	Date Reviewed: 21-01-2014	Revision: 01
---------------------------	-------------------------	---------------------------	--------------

Kenson Lubricants Limited Arvan House | Brookfield Drive | CANNOCK | Staffordshire WS11 0JN. Tel 01543 -500640 Fax 01543 500641
E-Mail sales@kensonlubricants.com technical@kensonlubricants.com Website: www.kensonlubricants.com