



your local global brand

Gulf EP Lubricant HD 150

Heavy Duty Industrial Gear Oil

Product Description:

Gulf EP Lubricant HD 150 is a high performance extreme pressure gear oil developed for the lubrication of heavy duty industrial gears working under severe operating conditions and is blended from high quality base stocks and sulphur-phosphorous type extreme pressure additives that gives excellent load carrying capability to provide protection against shock loading and wear.

The high thermo-oxidative stability of Gulf EP Lubricant HD 150 helps resist high temperature deposit formation and oil thickening. In addition, Gulf EP Lubricant HD 150 also possesses excellent water separation characteristics and offers resistance to foaming.

Gulf EP Lubricant HD 150 has excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs. High thermo-oxidative stability helps to resist deposit formation, provides enhanced system cleanliness and enables longer service intervals. Gulf EP Lubricant HD 150 provides effective rust and corrosion protection to all gearbox components and the excellent demulsibility properties enables trouble-free operation in conditions encountering water/moisture.

Gulf EP Lubricant HD 150 is applicable in a wide range of industrial spur, helical, bevel and steel-on-steel worm gears, in heavy-duty industrial enclosed gears operating under heavy or shock loading conditions and requiring extreme pressure performance, in journal and roller contact industrial bearings operating at low speeds and high loads and is suitable for splash, mist and circulating systems and suitable for marine gear applications.

Meets the specifications of:

ISO 12925-1 Enclosed Gears of Category CKC
DIN 51517 Part 3 – Lubricating Oils CLP
AGMA 9005-E02 – Extreme Pressure Gear Lubricants
David Brown S1.53 101 (E – Industrial Extreme Pressure Additive Oils)
AIST (US Steel) Requirements No. 224 Lead Free EP Gear Oil

<u>Properties:</u>	<u>Test Methods:</u>	<u>Typical Values:</u>
ISO Viscosity Grade	ISO 3448	150
Density @ 15°C	ASTM D4052	896 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D445	135-165 mm ² /s (cSt)
Viscosity Index	ASTM D2270	>95
Flash Point	ASTM D92	>220°C
Pour Point	ASTM D97	<-15°C
FZG A/8.3/90, Load Stage Fail	DIN 51354-2	>12
Rust Test	ASTM D665A/B	Pass
Copper Corrosion	ASTM D130	1a
Water Separability @ 82°C	ASTM D1401	Pass
Product Code: 2610	Date Issued: 05/07/2012	Date Superseded: 23/12/2011
		Revision nr: 02

Kenson Lubricants Limited Arvan House | Brookfield Drive | CANNOCK | Staffordshire WS11 0JN.Tel 01543 -500640 Fax 01543 500641
E-Mail sales@kensonlubricants.com technical@kensonlubricants.com Website: www.kensonlubricants.com



distributor of Industrial Lubricants by

