



GULF METALWORKING FLUIDS

your local global brand

GULFCUT 26-UA

Medium Viscosity general purpose neat cutting oil

A medium viscosity neat oil designed for general purpose machining of all metals. The product contains a synergistic blend of inactive chlorinated additives and synthetic esters to significantly enhance surface finish and tool-life even on difficult to machine alloys. Gulfcut 26-UA is non-staining, and can be used on yellow metals.

Benefits

Good lubricity

Good EP Performance.

Cost effective

Non-staining

Low foam, low mist

Excellent surface finish

Good Tool-life

Very economical in-use

Suitable for yellow metals.

Can be used on high pressure machines

Typical Physical Properties

Appearance	Amber fluid
Specific Gravity	~0.9 @ 20°C
Foaming Tendency	Low
Viscosity at 40°C	22 cSt
Lubricity	High
Chlorine (elemental)	2 – 5%
Sulphur (active)	Nil
Usage Concentration	As supplied

Application Method

GULFCUT 26-UA is suitable for grinding, sawing and machining of ferrous and non-ferrous metals, giving superior surface finish and tool –life. It can be used as a medium duty general-purpose workshop lubricant.

GULFCUT 26-UA can top-up all common neat metalworking fluids without adverse effect.

Storage:

- Store in a cool, well ventilated area
- Store inside, ideally between 10°C and 30°C
- Store away from direct heat and frost
- Shelf life 12 months from the date of manufacture
- Avoid water collecting on the barrel top

Kenson Lubricants Limited Arvan House | Brookfield Drive | CANNOCK | Staffordshire WS11 0JN

Tel 01543 -500640 Fax 01543 500641

E-Mail sales@kensonlubricants.com

technical@kensonlubricants.com

Website: www.kensonlubricants.com