



# GULF METALWORKING FLUIDS

your local global brand

## GULFCUT 26-UB

*High performance low viscosity neat honing oil suitable for all metals*

### Description

Gulfcut 26-UB is a high performance product manufactured from highly refined low viscosity mineral oil and containing extreme pressure performance additives together with additional wetting-out fortifiers.

### Application and Suitability

GULFCUT 26-UB has been designed for use in honing operations on all materials and can also be used for general machining of non-ferrous metals. This product is also suitable for use with cast iron and where rapid removal of fine particles to prevent wheel clogging is a particular requirement. GULFCUT 26-UB can also be used for a wide range of applications including lapping and light to moderate duty machining. This product contains a synergistic blend of inactive chlorine extreme pressure additives and synthetic esters and will not stain aluminium or yellow metals.

### Benefits

- Suitable for all metals
- Excellent lubricity
- Enhanced tool life
- Low viscosity for rapid fines removal
- Non staining on yellow metals
- High extreme pressure properties
- Excellent surface finish
- Excellent wetting properties

### Typical Physical Properties

|                     |                  |
|---------------------|------------------|
| Appearance          | Pale Clear Amber |
| Specific Gravity    | ~0.870           |
| Flash Point         | 138°C            |
| Viscosity at 40°C   | 5 cSt            |
| Lubricity           | Very High        |
| Usage Concentration | As supplied      |

### Storage:

- Store in a cool, well ventilated area
- Store inside, ideally between 10°C and 30°C
- Store away from direct heat and frost
- Shelf life 12 months from the date of manufacture
- Avoid water collecting on the barrel top