



GULF METALWORKING FLUIDS

your local global brand

GULFCUT 76-UB

High performance neat tapping and threading oil

Description

Gulfcut 76-UB is a high performance tapping and threading fluid suitable for all metals. The product gives superior surface finish and tool-life.

Benefits

- Excellent lubricity
- Excellent EP Performance.
- Suitable for all metals
- Highly treated
- Excellent surface finish
- Enhanced Tool-life
- Very economical in-use
- Suitable for difficult alloys

Suitability

GULFCUT 76-UB is suitable for tapping and threading of all ferrous and non ferrous metals and alloys, including modern aerospace type materials, and aluminium alloys.

GULFCUT 76-UB can top-up all common neat metalworking fluids without adverse effect

Typical Physical Properties

Appearance	Brown fluid
Specific Gravity	~0.95 @ 20°C
Foaming Tendency	Low
Viscosity at 40°C	37 cSt
Lubricity	Very High
Chlorine (elemental)	15 – 30%
Sulphur (active)	3-5%
Usage Concentration	As supplied
Flash Point	210°C

Storage:

- Store in a cool, well ventilated area
- Store inside, ideally between 10°C and 30°C
- Store away from direct heat and frost
- Shelf life 12 months from the date of manufacture
- Avoid water collecting on the barrel top

Kenson Lubricants Limited Arvan House | Brookfield Drive | CANNOCK | Staffordshire WS11 0JN. Tel 01543 -500640 Fax 01543 500641

E-Mail sales@kensonlubricants.com

technical@kensonlubricants.com

Website: www.kensonlubricants.com