



GULF METALWORKING FLUIDS

your local global brand

GULFCUT 79-UE

High performance low viscosity honing and lapping oil for ferrous metals

Description

Gulfcut 79-UE is a high performance honing oil. It is based on high quality, low viscosity base oils with a blend of carefully selected synergistic fatty sulphurised and chlorinated additives which provide excellent high temperature performance.

The nature of the extreme pressure/lubricity package utilised in Gulfcut 79-UE ensures prolonged tool life and a superior surface finish on fine tolerance work. In addition the low viscosity will allow maximum penetration and heat dissipation.

Benefits

- Excellent lubricity
- Excellent EP performance.
- Cost effective
- Highly treated
- Safe and pleasant to use
- Enhanced tool-life
- Enhanced surface finish
- Low foaming

Typical Physical Properties

Appearance	Dark fluid
Specific Gravity	~0.87 @ 20°C
Foaming Tendency	Low
Viscosity at 40°C	5 cSt
Lubricity	High
Usage Concentration	As supplied

Application Method

Gulfcut 79-UE is suitable for a wide range of applications including honing, lapping and light to moderate duty machining on ferrous materials.

Due to the active nature of the extreme pressure additives, this product is not recommended for yellow metals.

Storage:

- Store in a cool, well ventilated area
- Store inside, ideally between 10°C and 30°C
- Store away from direct heat and frost
- Shelf life 12 months from the date of manufacture
- Avoid water collecting on the barrel top