



Gulf Pride 4T

4-Stroke Motorcycle Oil

Product Description

Gulf Pride 4T is a high quality 4-stroke gasoline engine oil developed specifically to meet the special requirements of air cooled 4-stroke motorcycles. It is blended from highly refined base oils and performance additives to provide protection to engine, gear box and wet clutch used in 4-stroke motorcycles. The product exceeds the international specifications of API SG and JASO MA for 4-stroke motorcycle oils and the requirements of leading global 4-stroke motorcycle manufacturers. It is available in five different viscometrics, viz SAE 10W-40, SAE 15W-40, SAE 15W-50, SAE 20W-40 and SAE 20W-50.

Features & Benefits

- Excellent antiwear properties protect vital engine and gear components leading to reduced maintenance costs
- Good thermo-oxidative stability prevents harmful deposit formation and controls oil thickening facilitating extended engine and oil life
- Controlled frictional properties eliminate clutch slippage and improves drivability
- Better detergency/ dispersancy keeps engine cleaner and reduces maintenance costs
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications

- Recommended for air cooled 4-stroke motorcycle engines where an API SG and JASO MA quality oil is required
- Also suitable for small 4-stroke gasoline engines used in portable generators, pumps, garden machinery and other applications

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-40	15W-40	15W-50	20W-40	20W-50
API SG, JASO MA		X	X	X	X	X
Has the following On File Status						
JASO MA					X	X
Typical Properties						
Test Parameters	ASTM Method	Typical Values				
Viscosity @ 100 °C, cSt	D 445	14.6	14.2	18.3	14.4	18.6
Viscosity Index	D 2270	160	137	147	119	126
Flash Point, °C	D 92	234	232	236	254	256
Pour Point, °C	D 97	-33	-24	-24	-24	-24
TBN, mg KOH/g	D 2896	7.1	7.1	7.1	7.1	7.1
Density @ 15°C, Kg/l	D 1298	0.877	0.871	0.869	0.895	0.894
Sulphated Ash, %wt	D 874	0.85	0.85	0.85	0.85	0.85